



CESPEX Lighting Co.,Ltd

Branch Office: Room1501, No.28-29 Lianyou building, Fulian 2nd area, Sanlian community, Longhua road, Longhua district, Shenzhen, Guangdong, China. (518109)
 Headquarter: Room6001-6009, 6th Floor Wangcheng Building, Longguan East Road, Longhua District, Shenzhen city 518109, China.
 Factory: No.273, Tangxia Road, Fenghuang Hilllock, Tangxia Town, Dongguan City, Guangdong Province, China
 E: sales@cesp-industrial.com T: 0086 13267157712 Skype: CESP-5 Web: www.cesp-industrial.com

LED EXPLOSION PROOF LIGHT

Product Image	Model	Parameters		LED chips	Driver	Warranty
	CES-RY-DFG-40W	Power: 40W	Dimensions: Ø150*H280mm	Epistar 3030 112pcs	MOSO AC100-240V	3 Years
		Color Temperature:3000K-6500K	IP level: IP65			
		CRI: ≥80Ra	Beam angle: 220°	Lumileds/Osram 3030-112pcs		5 Years
		Power Factor: ≥0.97	Corrosion proof level: WF2			
		Lumen Output: 4620LM±5%	Thread size: G3/4			
Net Weight: 3.2KG	Life span: 30000H-50000H					
	CES-RY-DFG-60W	Power: 60W	Dimensions: Ø150*H280mm	Epistar 3030 112pcs	MOSO AC100-240V	3 Years
		Color Temperature:3000K-6500K	IP level: IP65			
		CRI: ≥80Ra	Beam angle: 220°	Lumileds/Osram 3030-112pcs		5 Years
		Power Factor: ≥0.97	Corrosion proof level: WF2			
		Lumen Output: 8250LM±5%	Thread size: G3/4			
Net Weight: 3.5KG	Life span: 30000H-50000H					
	CES-RY-DFG-80W	Power: 80W	Dimensions: Ø190*H300mm	Epistar 3030 224pcs	MOSO AC100-240V	3 Years
		Color Temperature:3000K-6500K	IP level: IP65			
		CRI: ≥80Ra	Beam angle: 220°	Lumileds/Osram 3030-224pcs		5 Years
		Power Factor: ≥0.97	Corrosion proof level: WF2			
		Lumen Output: 10400LM±5%	Thread size: G3/4			
Net Weight: 4.2KG	Life span: 30000H-50000H					
	CES-RY-DFG-120W	Power: 120W	Dimensions: Ø190*H300mm	Epistar 3030 224pcs	MOSO AC100-240V	3 Years
		Color Temperature:3000K-6500K	IP level: IP65			
		CRI: ≥80Ra	Beam angle: 220°	Lumileds/Osram 3030-224pcs		5 Years
		Power Factor: ≥0.97	Corrosion proof level: WF2			
		Lumen Output: 15600LM±5%	Thread size: G3/4			
Net Weight: 4.2KG	Life span: 30000H-50000H					

LED canopy light/gas station light

Product Image	Model	Parameters		LED chips	Driver	Warranty	
	CES-GL-50W-D	Power: 50W	Dimensions: 194*350*115mm	Epistar 3030 56pcs	Common AC85-265V	3 Years	
		Color Temperature: 3000K-6500K	IP level: IP65				
		CRI: ≥80Ra	Beam angle: 30°/60°/90°/80°150°	Lumileds/Osram 3030-56pcs		MW AC100-305V	5 Years
		Power factor: ≥0.97	Packing size: 26*40*17CM				
		Lumen output: 6000LM±5%	Package: 1PCS/CTN				
N.W.: 3KG	G.W.: 3.5KG						
	CES-GL-100W-D	Power: 100W	Dimensions: 280*350*115mm	Epistar 3030 112pcs	Common AC85-265V	3 Years	
		Color Temperature: 3000K-6500K	IP level: IP65				
		CRI: ≥80Ra	Beam angle: 30°/60°/90°/80°150°	Lumileds/Osram 3030-112pcs		MW AC100-305V	5 Years
		Power factor: ≥0.97	Packing size: 33*40*17CM				
		Lumen output: 12000LM±5%	Package: 1PCS/CTN				
N.W.: 4.5KG	G.W.: 5.2KG						
	CES-GL-150W-D	Power: 150W	Dimensions: 366*350*115mm	Epistar 3030 168pcs	Common AC85-265V	3 Years	
		Color Temperature: 3000K-6500K	IP level: IP65				
		CRI: ≥80Ra	Beam angle: 30°/60°/90°/80°150°	Lumileds/Osram 3030-168pcs		MW AC100-305V	5 Years
		Power factor: ≥0.97	Packing size: 41*40*17CM				
		Lumen output: 18000LM±5%	Package: 1PCS/CTN				
N.W.: 5.8KG	G.W.: 6.6KG						
	CES-GL-200W-D	Power: 200W	Dimensions: 452*350*115mm	Epistar 3030 224pcs	Common AC85-265V	3 Years	
		Color Temperature: 3000K-6500K	IP level: IP65				
		CRI: ≥80Ra	Beam angle: 30°/60°/90°/80°150°	Lumileds/Osram 3030-224pcs		MW AC100-305V	5 Years
		Power factor: ≥0.97	Packing size: 45*40*17CM				
		Lumen output: 24000LM±5%	Package: 1PCS/CTN				
N.W.: 7KG	G.W.: 7.8KG						

Remark: 1. High luminous efficacy/Dimmable function are customizable.

2. EXW factory price term, air freight or sea freight depends on order quantity.

3. Sample production time estimated 5-7 working days, mass production 10-15 working days (depend on quantity).

4. Payment term: 100% T/T via company account for small order, 30% deposit for big order.